

# HCVR5104H-V2



## HDCVI

### Technical Specifications

System		
Main Processor		Embedded processor
Operating System		Embedded LINUX
Video		
Standard		NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Audio		
Input		1 channel, RCA
Output		1 channel, RCA
Two-way Talk		Reuse audio input/output channel 1
Display		
Interface		1 HDMI, 1 VGA,
Resolution		1920×1080, 1280×1024, 1280×720, 1024×768, 800×600
Privacy Masking		4 rectangular zones (each camera)
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording		
Video/Audio Compression		H.264 / G.711
Resolution		720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF(704×576 /704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)
Record Rate	Main Stream:	720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)
	Extra Stream	CIF/QCIF(1~25/30fps)
Bit Rate		48~6144Kb/s
Record Mode		Manual, Schedule(Regular(Continuous), MD), Stop
Record Interval		1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection		
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Playback & Backup		
Sync Playback		1/41/4/8
Search Mode		Time/Date, MD & Exact search (accurate to second)
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode		USB Device / Network
Network		
Ethernet		RJ-45 port (10/100M)

### Dimensions(mm):

